




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H04M 1/00, G06F 17/30, H04M 7/00	A1	(11) International Publication Number: WO 99/56447 (43) International Publication Date: 4 November 1999 (04.11.99)
(21) International Application Number: PCT/US99/08217 (22) International Filing Date: 15 April 1999 (15.04.99) (30) Priority Data: 09/069,716 29 April 1998 (29.04.98) US (71) Applicant: INFOGEAR TECHNOLOGY CORPORATION [US/US]; Suite 200, 2055 Woodside Road, Redwood City, CA 94061 (US). (72) Inventors: GIORDANO, Joseph, III; 205 Belmont, Redwood City, CA 94061 (US). SAMBOURSKY, Jacob; 30b Ig'al Alon street, Herzelia (IL). (74) Agents: GLENN, Michael, A. et al.; Glenn Patent Group, 125 Lake Road, Portola Valley, CA 94028 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>

(54) Title: METHOD AND SYSTEM FOR CONFIGURING AN INTERNET APPLIANCE



(57) Abstract

The Internet appliance accesses an HTML page on a Web site containing configuration information for an Internet appliance such as an Internet compatible telephone. Data from the HTML page are downloaded to the Internet appliance to modify its options or settings automatically upon accessing the HTML page, or as directed by the user. The data may be downloaded to a programmable memory in the Internet appliance and the stored data may be used to upgrade the Internet appliance. The upgrade HTML page may include information to alert the user when the new information is available regarding changes to options and settings of the Internet appliance. Alternatively, data from the Internet appliance are placed in an HTML page and the data are then uploaded to the Web site. Additional embodiments provide other functions that may be placed in an HTML page to effect some internal action in the Internet appliance, such as checking e-mail.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

METHOD AND SYSTEM FOR CONFIGURING AN INTERNET APPLIANCE

BACKGROUND OF THE INVENTION

5

TECHNICAL FIELD

The invention relates to electronic communication systems. More particularly, the invention relates to a system for upgrading and configuring an Internet appliance from
10 databases distributed over an electronic network.

DESCRIPTION OF THE PRIOR ART

Electronic networks are increasingly used to store and distribute a variety of data.
15 Examples of such electronic networks include the Internet, and intranet systems. For example, World Wide Web (Web) pages (which may be accessed over the Internet) may include text, graphical displays, video displays, animation, and sounds.

The Web is usually accessed via telephone lines by a modem-connected computer.
20 However, the Web may also be accessed through other devices, including personal data assistants, fax machines, and Internet-compatible telephones. One telephone that provides Web access is described in M. Valentaten, B. Moeschen, Y. Friedman, Y.-T. Sidi, Z. Blkowsky, Z. Peleg, *Multi-Mode Home Terminal System that Utilizes a Single Embedded General Purpose/DSP Processor and a Single Random Access*
25 *Memory*, U.S. Patent No. 5,250,940 (October 5, 1993).

A Web page is encoded in Hypertext Markup Language (html). An html document is a plain-text (ASCII) file that uses tags to denote the various elements in the document. An element may include an attribute, which is additional information that is included
30 between tags.

HTML can be used to link text and/or images, such as icons, to another document or section of a document. The user activates a link by clicking on it, and the linked database is directly accessed. Links are used to access related information, or to
35 contact a person or entity. However, information on a Web page must have the requisite html tags to provide an active link.

It is known to download modifications to computer software from the Web. The user selects a hypertext link on a Web page and the appropriate data is downloaded to the

user's computer. The user then uses the downloaded data to upgrade the computer. However, such downloads are typically either software applications or graphical representations, such as icons.

5 A Web page may also provide other useful information. For example, various settings, such as an Internet Service Provider's (ISP) access telephone number may be stored on a Web page. However, the user must still manually configure the computer to change this information locally. In addition to the options and settings necessary to connect to the Web, such Internet appliances as an Internet-compatible
10 telephone also require settings for telephone functions. Such telephone functions include service features, such as Caller ID or Call Waiting, as well as the graphical user interface for displaying the telephone functions, and user profile configuration information, such as how to dial, local area code, and the user's name, address, and zip code.

15 An Internet appliance, such as the Internet-compatible telephone, typically is limited processing power and memory storage, as compared to a computer. Thus, it is advantageous to minimize the power and memory required to modify the configurations and features of the appliance.

20 It would therefore be an advantage to provide a method and system for automatically configuring an Internet-compatible telephone from the Internet. It would be a further advantage if such method and system minimized the processing power and memory storage required for such upgrade.

25

SUMMARY OF THE INVENTION

The invention provides a method and system for automatically configuring an Internet appliance from a Web page, *i.e.* via an html page. The invention is modified variables
30 that include, options, settings, and supported features, as well as the graphical user interface for the Internet appliance. Such variable may consist of, for example, Internet Service Provider (ISP) telephone numbers, user's area code, name, address, and zip code and such calling features as call waiting, call forwarding, and last call returned. Uniquely, the features provided by the invention are implemented by a novel put/get
35 mechanism.

The preferred embodiment of the invention is adapted for use with the Internet appliance described above (see U.S. Patent No. 5,250,940.) However, alternative embodiments of the invention are adapted for use with any Internet access device. In

the preferred embodiment, the Internet appliance accesses a special HTML page on a Web site containing configuration information for the appliance. This HTML page is used to modify the Internet appliance.

5 In one embodiment of the invention, data from the HTML page are downloaded to the Internet appliance to modify its options or settings automatically upon accessing the page. However, in the preferred embodiment of the invention, the HTML page includes special tags that direct the Internet appliance to perform certain operations. The user then selects the desired options and settings and the Internet appliance is
10 adjusted accordingly per the definitions contained in the HTML page.

In an alternative, equally preferred embodiment, the upgrade data are downloaded from the HTML page to programmable memory in the Internet appliance. The stored data are then used to upgrade the Internet appliance.

15 HTML pages containing configuration data for the Internet appliance may be stored on a server, or on any computer accessible via the Internet. For example, the server may maintain a cache of Web pages frequently accessed by the Internet appliance, such as HTML pages containing configuration data.

20 In one embodiment of the invention, an upgrade Web page alerts the user when new information regarding changes to options and settings of the Internet appliance are available. Equipment or service companies, such as a telephone company, can provide HTML pages on their Web sites to make upgrades available to its users. A
25 user then selects new features, such as Call Forwarding, or upgrades existing services directly from the telephone company.

In a preferred embodiment of the invention, telephone service information is automated. In this embodiment, a selectable area is provided on a graphical user
30 interface of the Internet appliance. When this area is selected, the Web page for the desired service is automatically accessed, and the data are downloaded.

A profile of the Internet-compatible telephone user may be stored in the Internet appliance. The HTML page uses this profile to provide customized services. For
35 example, the users profile information can be retrieved from the Internet appliance and sent to a Web site to provide personalized or localized services.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram of an Internet-compatible telephone connection to the Internet according to a preferred embodiment of the invention;

Fig. 2 is a flowchart of the method for configuring an Internet appliance according to the invention;

Fig. 3 is a schematic representation of an HTML page showing a put operation according to the invention; and

Fig. 4 is a schematic representation of an HTML page showing a get operation according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

The invention provides a method and system for automatically configuring and/or querying an Internet appliance from a Web page. The invention is a user-friendly and efficient method and system for configuring the options and settings of an Internet appliance, such as an Internet-compatible telephone. Additionally, the invention is also operable to modify the features supported by the Internet appliance, as well as the graphical user interface for the appliance display. The preferred embodiment of the invention is adapted for use with an Internet appliance (see U.S. Patent No. 5,250,940.) However, alternative embodiments of the invention are adapted for use with any Internet access device.

The Web is usually accessed via telephone lines by a modem-connected computer, or Internet access appliance. The client dials up an Internet Service Provider (ISP), for example using the Point-to-Point protocol (PPP). In turn, the ISP host establishes the connection to the Internet.

Fig. 1 is a diagram of an Internet-compatible telephone showing a connection to the Internet according to the invention. The internet-compatible telephone 10 uses a modem 12 to dial-up a modem 14 at the ISP's local point-of-presence (POP). This modem 12 transmits information from the client to a server 16 residing on the ISP's local area network (LAN) 18. The server uses Hypertext Transfer Protocol (HTTP) and TCP/IP protocol 20 to communicate, via a datalink 22 to the Internet 24. The Internet-

compatible telephone displays the information retrieved from the Internet on its display screen 26 using a browser application 28.

5 Fig. 2 is a flowchart of the method for configuring an Internet appliance according to the invention. For example, an Internet-compatible telephone has many settings within it that control functions of the telephone. Such settings include the telephone numbers for dialing in to the ISP network, user names, profile information, local default pages, as well as settings for handling connecting and disconnecting, time outs, and special calling features related to the telephone portion of the appliance, such as call waiting and call forwarding.
10

To reconfigure these options and settings, the Internet-compatible telephone is connected to a Web site (100) containing configuration information for the telephone. The Internet-compatible telephone then accesses an HTML page (105) on that Web site. This HTML page is used to configure the Internet-compatible telephone.
15

In one embodiment of the invention, data from the HTML page are downloaded to the Internet-compatible telephone to reconfigure its options or settings automatically. However, in the preferred embodiment of the invention, the HTML page includes special tags that direct (110) the Internet-compatible telephone to perform certain operations. Such operations include requesting the user to answer questions on a form, or to choose options from a table.
20

The user then selects (115) the desired options and settings. In a preferred embodiment of the invention, the settings provided by the HTML page include special HTML codes that automatically adjust (120) the Internet-compatible telephone accordingly. In an alternative, equally preferred embodiment, the data are downloaded (125) from the HTML page to programmable memory, such as flash memory, in the Internet-compatible telephone. The data stored in the flash memory are then used to configure (130) the Internet-compatible telephone. This foregoing operation may be implemented using a unique put/get mechanism (discussed below).
25
30

The preferred embodiment of the invention may also implement a security scheme to prevent the intentional corruption of the information contained within the Internet appliance, for example, by a virus, or as a result of an unauthorized or unintentional reconfiguration request.
35

In one embodiment of the invention, the upgrade Web page includes information that alerts the user when the HTML page contains new information regarding changes to

options and settings of the Internet-compatible telephone. The user may select particular options or settings for which the user wishes to receive notification, or the user may be notified of all changes to the options or settings. The Internet-compatible telephone may then either be automatically reconfigured with these changes, or reconfigured at the user's discretion.

Any HTML page may be created with the special tags that are required to reconfigure and/or query Internet-compatible telephone functions. Thus, equipment or service companies, such as a telephone company, can provide such HTML pages on their Web sites. A user then selects new features, such as Call Forwarding, or upgrades existing services directly from the telephone company.

In a preferred embodiment of the invention, a selectable area is provided on a graphical user interface of the Internet appliance, such as a slide-up window. The user selects the area, the Web site maintaining the HTML page for the desired service is automatically accessed, and the data are downloaded from the server to the Internet appliance to effect modification of the Internet appliance.

The HTML page can also include hyperlinks to other sites of interest to the user. In one embodiment of the invention, each linked HTML page provides the user with additional information and options. When the user decides to make a particular change, another hyperlink may be selected to implement the change. Such hyperlinks can be to more than one server site. For example, a user who desires to change the Internet-compatible telephone browser application to Japanese settings could select a hyperlink to a server in Japan.

Uniquely, the invention provides a novel mechanism that supports both HTML push and pull data transmission between the Internet and the Internet appliance, and that provides automated functions therefore. Such functions can include, for example an upgrade or reconfiguration of the Internet appliance, checking e-mail, putting information, and getting information. With regard to configuration, the mechanism provides for the setting and resetting of various user preferences or system required preferences (for example an Intranet that has been customized for a particular company's requirements). Further, functionality can include monitoring functions such as checking variables and getting the state of an upgrade. For example, such monitoring functions may be used to determine if the Internet appliance does not include the most recent version of a particular operating element.

In connection with the put/get function, a server shows a configuration Web page. The Internet appliance is operable to put information, such as field information, into its local nonvolatile memory. Alternatively, the server can transparently put this information into the Internet appliance's nonvolatile memory. Uniquely, this information is derived from the contents of the HTML page.

With regard to the get function, the server may show an HTML page in which there is a get function. The Internet appliance may place values into this HTML page, *i.e.* substitute them into the HTML page dynamically before redisplaying the page locally. Thus, the Internet appliance gets information from its nonvolatile memory and substitutes it into an HTML page. The Internet appliance can send the HTML page with the information that was received (gotten) from the nonvolatile memory and return the HTML page to the server.

In summary, the put/get functions allow the placing of information, from the Internet appliance into a form and/or the putting of information from any other form into the Internet appliance. For example, a telephone company may provide a calling feature page (see Fig. 3). Such page may query the user as to what calling features are desired. The user would check those features. In Fig. 3, the user has checked call waiting and call forwarding. The user would also complete a registration page. When the form is completed, the HTML information that is sent from the telephone company server includes configuration information for the Internet appliance that is put into the Internet appliance, such that the telephone function with the Internet appliance is configured for call waiting and call forwarding functions. In the preferred embodiment of the invention, this information would be placed into a flash EEPROM or other such storage device in the Internet appliance.

Fig. 4 shows an example of a get function. In this example, a search page is shown that is presented at the Internet appliance pursuant to a Yellow Pages search. With regard to certain fields within the form, the Internet appliance may have been configured to supply information to complete the form. For example, for each search, the form automatically confines the search to the State of Arkansas because the Internet appliance is located in Arkansas and it is assumed that a Yellow Page search is conducted locally. In such case, each time the search page for the Yellow Pages is retrieved, the HTML mechanism gets the state information from memory within the Internet appliance. In this way a default is established.

Additionally, the put/get functions may be used with regard to variables, for example with regard to configuration of the Internet appliance and the operating status for various

Internet appliance features (for example is the Internet appliance operating properly). Finally, the put/get functions may be used within an Intranet, for example to configure the Internet appliance to a company's particular requirements.

- 5 The following provides two examples of the put/get mechanism in accordance with the invention.

Example 1

- 10 An HTML file for the Get / Put mechanism of internal client parameters:

```
<HTML>
```

```
<pre>
```

```
<FORM action="iph://phone/cfg_put">
```

```
  user name: <INPUT type=text  name="cfg_isp_user_name" >
```

- 15 <INPUT type=hidden name="cfg_isp_phone" value="1-408-1234">

```
<INPUT type=submit value=put>
```

```
</FORM>
```

```
<FORM action="http://www.infogear.com/mydirectory/myscript.cgi">
```

- 20 user name: <INPUT type=text name="my_username"

```
value="%cfg_isp_user_name">
```

```
<INPUT type=hidden name="my_dialin"  value="%cfg_isp_phone">
```

```
<INPUT type=submit value=get>
```

```
</FORM>
```

25

```
</pre>
```

```
</HTML>
```

Explanation

30

This file includes two forms, the first for 'put' (write new values for configuration parameters, and the second for 'get' (read information from configuration parameters).

In the first form there are two variables that are written as soon as the user presses the submit button. The first variable is the 'user name' setting on the Internet appliance. In

- 35 the example, the user is required to input his name. The second variable is the telephone number of the ISP. In the example above, the number is fixed, and is hidden from the user.

In the second form, there are two variables that are read as soon as the user presses the submit button, and are sent to the user's script called 'myscript'. The first variable is the 'user name' setting on the Internet appliance. In the example, the user can change the name, using the internal name as default. The second variable is the phone number of the ISP. In the example above, the telephone number is read automatically without the user knowledge.

Example 2

10 An HTML file for Internet appliance internal function call from within an HTML file:

<HTML>

<FORM action="iph://phone/dial">

15 Phone to dial: <INPUT type=text name="p" value="1-408-1234">

<INPUT type=submit value=dial>

</FORM>

 Dial link

20

</HTML>

Explanation

25 The example uses the telephone internal 'dial' function. The first section is a form that allows the user to type a telephone number to dial in an edit box. The second section is a link that dials a fixed telephone number.

30 The invention is best appreciated when it's considered that HTML is currently the content of a particular page and the format. In the invention, HTML is a part of a program in that the HTML tags themselves perform programming functions, such as configuration or completion of a form. In previous uses of HTML, these functions were preformed by a user, for example in response to instruction contained and read from an HTML page by a user. In this regard, the invention is seen as being broadly applicable to any type of programming environment, for example where the HTML code may be used to provide a user interface for an embedded device. In this case the HTML is the user interface and the uniform resource locators are functions of a program within the user interface. For example, an HTML front end may be provided as a user interface to a C code program. In such case, there is no need to compile the

35

user interface and the user interface is therefore portable and readily accessible. This is particularly true because HTML is relatively simple programming language. In this regard, a user interface may be provided with a more complex program, for example a word processing program or spreadsheet program written in C, in which case the user interface is readily customized by the user without the need to know the underlying programming language, *i.e.* C.

A URL in general is described in *Uniform Resource Locators (URL)*, RFC 1738 (www.23.org/addressing/RFC1738.txt). In accordance with the invention, a URL may be thought of as describing a protocol (for example, http) in which there is a host (the put or get location) and a particular location within the host (for example, flash memory). The URL is uniquely used to call internal functions of the device (either the client or the server) to get information or to put information as required. In connection with the Internet appliance, a particular URL may be used (for example i_ph:// or iPh://gw). In this example the host is the Internet appliance and the location within the Internet appliance is the function called (for example the setting of call waiting).

Additional applications of the herein disclosed invention include the calling of internal functions of the Internet appliance, when the Internet appliance is operating as a Web client, via HTML pages. For example, a uniform resource locator (URL) may be used to define resources or functions within the Web client, *e.g.* checking e-mail.

Although the invention is described herein with reference to the preferred embodiment, one skilled in the art will readily appreciate that other applications may be substituted for those set forth herein without departing from the spirit and scope of the present invention. For example, a profile of the Internet-compatible telephone user may be stored in the Internet-compatible telephone. The HTML page includes special functionality that accesses this profile to allow the system to provide customized services, such as the sending of certain material to the user. Accordingly, the invention should only be limited by the Claims included below.

CLAIMS

1. A method for automatically configuring a network appliance, comprising the
5 steps of:
 downloading data from an HTML page accessed during a session;
 parsing the HTML code of said downloaded data to determine an action and
identify configuration information to accompany said action;
 transmitting configuration information to said appliance; and
10 configuring said appliance with said configuration information in accordance with
said action.
2. The method of Claim 1, wherein said downloading step further comprises the
steps of:
15 storing said downloaded data in the memory of said Internet appliance; and
configuring said appliance from said stored data.
3. The method of Claim 1, further comprising the step of:
notifying said appliance when new information is available at said HTML page
20 regarding changes to said appliance.
4. The method of Claim 1, wherein said appliance is an Internet-compatible
telephone.
- 25 5. The method of Claim 1, further comprising the step of providing a selectable
area on a graphical user display of said Internet appliance, wherein said HTML page is
accessed in response to the selection of said area.
6. The method of Claim 1, further comprising the steps of:
30 storing a profile in said appliance; and
using said profile to customize said data downloaded to said appliance.
7. A system for automatically configuring a network appliance, comprising:
means for downloading data from an HTML page accessed during a session,
35 wherein said data include an action and configuration information for said appliance;
a parser for parsing the HTML code of said downloaded data;
means for transmitting configuration information obtained by parsing said HTML
code to said appliance; and

means for configuring said appliance with said configuration information in accesses with said action.

8. The system of Claim 7, further comprising;
5 a memory accessible to said appliance for storing said downloaded data, wherein said appliance is reconfigurable from said stored data.
9. The system of Claim 7, further comprising;
10 a notification module associated with said HTML page for notifying said appliance when new information regarding changes to said appliance is available on said HTML page.
10. The system of Claim 7, further comprising;
15 a selectable area on a graphical user display of said appliance, wherein said HTML page is accessed in response to the selection of said area.
11. The system of Claim 7, further comprising;
20 a profile stored in said appliance, wherein said profile is used to customize said data downloaded to said appliance.
12. The system of Claim 7, wherein said appliance is an Internet-compatible telephone;
13. A method for asserting an action at a network compliance, comprising the steps
25 of :
establishing a network connection between said appliance and a server, wherein said appliance accesses HTML pages resident at said server;
accessing such HTML pages with said appliance, wherein said HTML page includes at least one uniform resource locator (URL) having the format host; and
30 appliance function;
wherein said URL calls internal functions of said appliance.
14. The method of Claim 13, wherein said URL puts information into said appliance.
- 35 15. The method of Claim 13, wherein said URL gets information from said appliance.

16. A graphical user interface, comprising:
an HTML coded user interface portion;
wherein each uniform resource locator (URL) embedded in said HTML code
provides access to either of an entry point or exit point in an underlying computer
5 program.

1/4




FIG. 1

2/4




FIG. 2

3/4




FIG. 3

4/4




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 99/08217

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04M1/00 G06F17/30 H04M7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04M G06F H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 16051 A (MITEL CORP) 16 April 1998 (1998-04-16) page 2, line 7 - line 12 page 3, line 24 - line 25	1,2,5,7, 8,10,16
A	claim 1	3,4,6,9, 11-15
A	WO 98 11704 A (DIALNET INC) 19 March 1998 (1998-03-19) page 24, line 15 -page 25, line 1	11-15
A	WO 97 38511 A (AT & T CORP) 16 October 1997 (1997-10-16) page 10, line 22 - line 28	1-15
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

4 October 1999

Date of mailing of the international search report

12/10/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Schweitz, M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/08217

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 572 643 A (JUDSON DAVID H) 5 November 1996 (1996-11-05)	16
A	column 4, line 52 -column 5, line 5 figure 6	1-15
A	WO 97 16938 A (NOKIA TELECOMMUNICATIONS OY ;LEPPAENEN REIJO (FI)) 9 May 1997 (1997-05-09) page 3, line 8 -page 4, line 4	1-15
A	FUJINO N ET AL: "MOBILE INFORMATION SERVICE BASED ON MULTI-AGENT ARCHITECTURE" IEICE TRANSACTIONS ON COMMUNICATIONS, vol. E80-B, no. 10, 1 October 1997 (1997-10-01), pages 1401-1406, XP000734533 ISSN: 0916-8516 the whole document	1-16

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/08217

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9816051 A	16-04-1998	CA 2187240 A	07-04-1998
WO 9811704 A	19-03-1998	AU 4353097 A	02-04-1998
WO 9738511 A	16-10-1997	CA 2250789 A	16-10-1997
		EP 0894386 A	03-02-1999
US 5572643 A	05-11-1996	AU 699439 B	03-12-1998
		AU 7458896 A	07-05-1997
		CA 2235014 A	24-04-1997
		EP 0856180 A	05-08-1998
		WO 9715020 A	24-04-1997
		US 5737619 A	07-04-1998
WO 9716938 A	09-05-1997	FI 955188 A	24-06-1997
		AU 6877696 A	22-05-1997
		EP 0872138 A	21-10-1998